

FLR Flameproof Liquid Filled Radiators

The FLR range of liquid filled electrically heated radiators comes complete with an externally adjustable control thermostat, and is certified for use in hazardous areas where the atmosphere is classified as a Zone 1 or 2 (IIA, IIB, IIC) gas group, or a Zone 21 or 22 (IIIA, IIIB, IIIC) dust group.


FEATURES

- Certified to meet the ATEX Equipment Directive
- Low surface temperature
- Certified weatherproof protected to IP6X
- Integral preset surface temperature control thermostat
- Floor mounting
- Radiator filled with water / glycol mix
- Suitable for ambient temperatures from -20°C to +40°C
- Robust construction
- Manual reset over-temperature cut-out fitted to ensure radiator surface temperature never exceeds 80°C
- Optional externally adjustable control thermostat
- 2 × 25mm (plugged) cable entry provided as standard

TYPICAL APPLICATIONS


- Ammunition depots
- Explosive stores
- Chemical plant warehouses
- Firework factories
- Sugar refineries
- Laboratories
- Dusty environments





Model	Stock Code	Rating kW	Dimensions				Weight (kg)
			A	B	C	D	
FLR1	S63030001	1	580	510	N/A	N/A	50
FLR2	S63030002	2	1130	1035	510	550	100
FLR3	S63030003	3	1680	1575	780	830	150
FLR1A	S63040001	1	580	510	N/A	N/A	100
FLR2A	S63040002	2	1130	1035	510	550	150
FLR3A	S63040003	3	1680	1575	780	830	100

Certification

ATEX  II 2 G/D
 Ex d IIC T6 Gb (Gas) suitable for Zones 1 and 2
 Ex t IIIC T85°C Db (Dust) suitable for Zones 21 and 22
 CU TR (formerly GOST)

Enclosure

Cast aluminium finished in orange / grey

Radiator

Pressed steel with white powder coated finish to RAL 9010

Element

Long life 321 stainless steel rod-type, comprising high quality 80/20 nickel chrome resistance wire, compacted in magnesium oxide insulating powder

Controls

Preset radiator surface temperature control thermostat and manual reset safety temperature limiter (optional externally adjustable control thermostat)

Mounting

Floor standing with welded-on feet and wall retention brackets

Rating

Standard heater ratings 1kW, 2kW and 3kW

Voltage

1 phase: 230 to 240V